MICROTUNNEL DRILLING EQUIPMENTS

MICROTUNELING MACHINE:	AVN 2000

TECHNICAL SPECIFICATION	
AVN	2000
Outer diametr	3025
Max. tonque kNm	640
Rated Power KW	132
Weight	22 t



Note:	Made in Germany

MICROTUNELING MACHINE:	AVN 1600

TECHNICAL SPECIFICATION	
AVN	1600
Outer diametr	2150
Max. tonque kNm	310
Rated Power KW	110
Weight	17 t



Note:	Made in Germany

MICROTUNELING MACHINE:	AVN 1200 TB

TECHNICAL SPECIFICATION

Outer diameter, mm	1 505
Pipe OD, mm	1 490
Pipe ID, mm	1 200
Max. torque, kNm	258
Revolution LH / RH, rpm	0-6.7
Rated Power, kW	132
Steering cylinders	3
Force per cyl. / oil pressure, kN/bar	752/500
Drive length (recommended), m	500
Slurry line diam. mm	125



Note:	Made in Germany

MICROTUNELING MACHINE:	AVN 800

TECHNICAL SPECIFICATION

AVN	800
Outer diametr	1100
Max. tonque kNm	55
Rated Power KW	55
Weight	4,5 t



Note:	Made in Germany